



Steady Model

| | | GHS260E | GHS260H | GHS1012A | GHS103 |
|---|-----------|-------------|-------------|------------|-----------|
| | A | 241.5 | 221.5 | 463 | 241.6 |
| | B | 146.5 | 146.5 | 312 | 141.5 |
| | C | 56 | 56 | 115 | 73.5 |
| | D | 65 | 65 | 135 | 35 |
| | E | 128 | 128 | 262 | 106 |
| | F | 146 | 146 | 300 | 123 |
| | G | 44 | 44 | 85 | 50 |
| | I | 44 | 44 | 85 | 50 |
| | J | 23 | - | 25 | 35 |
| | K | 32 | 20 | 45 | 20 |
| | N | 44 | - | - | - |
| | P | 44 | 46.5 | 93.5 | 44 |
| | Q | 96 | 82.5 | 110 | 105 |
| | S | M12 X 1.75P | M12 X 1.75P | 18 | 14.5/9 |
| | U1 | 20 | 15 | 10 | 12 |
| | U2 | 60 | 45 | 120 | 29 |
| Clamping Ranges | U | 63 | 48 | 125 | 30 |
| Max. axial opening | d | 30 | 30 | 50 | 30 |
| Cylinder bore. | e | 1/4" | 1/4" | 1/4" | 1/4" |
| Hyd. Connection (BSP) | bar | 2-12 | 2-10 | 2-20 | 5-18 |
| Standard operating pressure | bar | 18 | 15 | 25 | 42 |
| Max. operating pressure | daN | 24 | 25 | 100 | 25 |
| Clam press./pad at 6 bar | daN | 100 | 100 | 1000 | 100 |
| Max. clamp pressure/pad. | mm | 0.01 | 0.005 | 0.01 | 0.02 |
| Centering accuracy over the whole clamping range. | mm | 0.002 | 0.002 | 0.003 | 0.003 |
| Repeatability | kg | 7 | 7 | 42 | 7 |
| Weight Approx. | | | | | |